

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

1.1 Safety Instructions

- WARNING!** Ensure Health & Safety, local authority and general workshop practice regulations are adhered to when using this equipment.
- ✓ Maintain the dent puller in good condition.
- ✓ Replace damaged parts. Use genuine parts only. Unauthorised parts may be dangerous and will invalidate the warranty.
- ✓ Use in a suitable work area. Keep area free from unrelated materials and ensure that there is adequate lighting.
- ✓ Before each use, check condition of dent puller. If any component is worn or damaged replace immediately.
- WARNING!** Always wear approved eye (or face) and hand protection when operating the puller.
- ✓ Remove ill fitting clothing. Remove ties, watches, rings, other loose jewellery and contain and/or tie back long hair.
- ✓ Maintain correct balance and footing. **DO NOT** over reach, ensure the floor is not slippery, wear non-slip footwear.
- ✓ Keep fingers clear of suction release trigger during use.
- ✓ Keep children and unauthorised persons away from the working area.
- ✓ Ensure workpiece is secure before operating the dent puller.
- ✓ Ensure that the workpiece surface is clean, dry and free from oil or grease.
- x **DO NOT** exceed the maximum pull capacity of the dent puller.
- x **DO NOT** clean the suction cups with solvents or other harsh chemicals.
- x **DO NOT** use the dent puller for any purpose other than that for which it is designed.
- x **DO NOT** use the dent puller if any parts are damaged or missing as this may cause failure and/or personal injury.
- x **DO NOT** use the dent puller when you are tired or under the influence of alcohol, drugs or intoxicating medication.
- ✓ When not in use, store in a safe, dry, childproof location.

2. INTRODUCTION & SPECIFICATION

2.1 Introduction

Specialist device for pulling dents from panels and bodywork. Contoured aluminium handle and suction release trigger give the technician close control.

2.2 Specification

Model No:	AK100	AK101	AK102
Size:	Ø75mm	Ø100mm	Ø125mm
Maximum Pull Capacity:	10kg	15kg	20kg

3. OPERATION

- WARNING!** Ensure that you read, understand and apply Section 1 safety instructions.
- 3.1 Ensure that the workpiece is clean, dry and free from oil and grease.
- 3.2 Remove the protective cover from the suction cup.
- 3.3 Holding the handle, firmly push the dent puller into the centre of the dent.
- 3.4 Pull the dent puller outwards in a controlled manner until the dent has been extracted.
- 3.5 Lift the suction release trigger to remove the dent puller from the workpiece.
- 3.6 Refit the protective cover on the suction cup and store in a safe, dry, childproof location.



4. MAINTENANCE

- 4.1 Check condition of suction cup regularly, if damaged replace using genuine parts only.
- 4.2 Keep dent puller in a clean, serviceable condition, use a damp cloth to clean.

Parts support is available for this product. To obtain a parts listing and/or diagram, please log on to www.sealey.co.uk, email sales@sealey.co.uk or phone 01284 757500.

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of this product.

WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.

INFORMATION: For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.