



INSTRUCTIONS FOR: OIL HOSE END GUN Model No: **AK4564D**

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will give you years of trouble free performance if these instructions are carefully followed and the product is correctly maintained.



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE RETAIN THESE INSTRUCTIONS FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

- p **WARNING!** Ensure health & safety, local authority, and general workshop practice regulations are strictly adhered to when using this equipment.
- 3 Familiarise yourself with product application and limitations, as well as the specific potential hazards peculiar to this product.
 - 3 Maintain the pump station in good condition (use an authorised service agent).
 - 3 Replace or repair damaged parts. *Use genuine parts only. Non authorised parts will invalidate the warranty.*
 - 3 Use only to dispense lubricants up to SAE 150 viscosity and antifreeze liquids.
 - 3 Ensure safety eye protection and protective clothing are worn when using this product.
 - 3 Keep the work area clean, uncluttered and ensure there is adequate lighting.
 - 3 Maintain correct balance and footing. Ensure the floor is not slippery and wear non slip shoes.
 - 3 Keep children and unauthorised persons away from the working area.
 - 3 After use, drain any fluids from the equipment before storage.
 - 3 Dispose of waste liquids in accordance with local authority regulations.
 - 3 Disconnect air pressure from equipment when not in use.
 - 7 **DO NOT** exceed the maximum working pressure of 1500psi.
 - 7 **DO NOT** point the nozzle at people or animals.
 - 7 **DO NOT** use the equipment near open flames.
 - 7 **DO NOT** smoke whilst using this equipment.
 - 7 **DO NOT** use to extract corrosive fluids.
 - 7 **DO NOT** dismantle, tamper with or adapt the gun for any purpose other than for which it is designed.
 - 7 **DO NOT** use the unit if it has been dropped or mishandled, check the unit to ensure there is no damage.
 - 3 Keep the gun and nozzle clean and store in a safe dry, childproof location.

p **WARNING! DO NOT** allow uncontrolled discharge of fluids thus polluting the environment. All liquids must be disposed of according to local authority regulations.

2. INTRODUCTION

Robust oil dispensing gun incorporating manual shut off. Fitted with rigid extension, handle lock and non-drip nozzle.

*Please note that this gun is not approved for resale of oil.


Model:	AK4564D
Maximum Flow Rate:	35ltr/min
Maximum Output Pressure:	1500psi
Inlet:	1/2" BSP

3. ASSEMBLY

- 3.1 Attach the nozzle assembly to the gun.
 - 3.2 Insert the filter into the inlet connection and then attach the supply hose.
- Note:** **DO NOT** overtighten the inlet swivel connection or damage may result.

4. OPERATION

- 4.1 Open the nozzle valve (fig.1).
 - 4.2 Press trigger to dispense liquid, the trigger can be locked open for long periods of dispensing using the clip.
- p **WARNING! DO NOT** leave the gun dispensing unattended.
- 4.3 Release the trigger to stop dispensing.
 - 4.4 Close the nozzle valve.



NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of product.

WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.

INFORMATION: Call us for a copy of our latest catalogue on 01284 757525 and leave your full name and address including your postcode.



Sole U.K. Distributor
Sealey Group
Bury St. Edmunds
Suffolk.



01284 757500

01284 703534



www.sealey.co.uk



sales@sealey.co.uk

AK4564D

Issue No: 1 - 14/11/08