

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY, AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

- ✓ Store in a dry easily accessible area.
- Be aware of the safety requirements (C.O.S.H.H.) for all stored fluids in your workshop.
- ✓ Wear safety equipment as advised in C.O.S.H.H. statements when using fluid or cleaning up after a spillage.
- ✓ Do mark on in indelible felt tip pen the fluid contained in the "HAZARDOUS WASTE ONLY" bag.
- ✓ Dispose of hazardous waste immediately and responsibly.
- **X DO NOT** use any single item in the kit more than once.
- **X DO NOT** use the kit for any purpose other than for which it is designed.
- X DO NOT use whilst eating, drinking, smoking; under the influence of drugs, alcohol, intoxicating medication, or if fatigued.

2. INTRODUCTION

These spill control kits have been designed to be a highly mobile solution when responding to spills and leaks as well as assisting companies in complying with current pollution prevention guidelines and other regulations. Suitable for use with oil, petrol, diesel, coolants, mild solvents, water and other spills. A full list of absorbent applications is provided in each kit. Supplied in a durable carry-case with a range of high quality absorbents, including high-grade polypropylene pads that can absorb up to 11tr of fluid and featuring a double weight cover sock for maximum absorbency. Also supplied with 1200mm long absorbent spills.

3. CONTENTS/SPECIFICATIONS

Model No SCK30

Item	Description	Qty
1	Pad (500mm x 400mm x 6mm)	18 (1ltr absorption per pad)
2	Sock (Ø75mm x 1200mm)	3 (5ltr absorption per sock)
3	Disposal bag	3
4	Bag tie	3




4. OPERATION

- 4.1 Shallow spills and final absorption of a spill should be carried out using pads, but only once it is ensured that containment is complete. The pads should be left in contact with the fluid for about two or three minutes, or until saturated. Each pad will contain up to one litre of fluid approximately, depending upon viscosity.
- 4.2 When using the absorbent Sock, it should be used to form a temporary dam to contain fluid and not as a mop. When two or more are used in a continuous length a nominal overlap of 300mm is suggested for a complete seal. (Larger spills would require the SCK50 kit)

5. DISPOSAL

- 5.1 Included in the kit are three large clearly marked disposal bags and associated ties. All used absorbents should be packed in these and the contents, indellibly marked in the spaces marked "PRODUCT" and "CATEGORY".
- 5.2 Dispose of immediately, following all local environmental guidelines.



WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.

INFORMATION: For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.



© Jack Sealey Limited 2013

SCK30 Issue: 1 - 02/01/13