

Thank you for purchasing a Sealey Product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

1.1. GENERAL SAFETY

- WARNING!** Ensure Health & Safety, local authority and general workshop practice requirements are adhered to when using this equipment.
- ✓ Use the pipe cutter in a suitable work area. Keep the area clean and tidy and ensure there is adequate lighting.
- WARNING!** Always wear approved eye or face protection when using the cutter.
- ✓ Keep children and unauthorised persons away from the work area.
- x **DO NOT** use the cutter for any purpose other than for which it is designed.
- x **DO NOT** use the cutter if any part of it is damaged or missing.
- x **DO NOT** allow untrained persons to use the cutter.
- x **DO NOT** attempt to cut piping when you are tired or under the influence of alcohol, drugs or intoxicating medication.
- ✓ When not in use, clean the cutter and store in a safe, dry, childproof area.
- 1.2 SAFETY REGARDING BRAKE FLUID.**
- ✓ Always read and comply with the warnings on the brake fluid manufacturer's container.
- ✓ Wear eye protection and keep skin contact to a minimum. If brake fluid enters eyes rinse with plenty of water and seek medical advice. If swallowed seek medical advice immediately.
- ✓ Dispose of waste brake fluid in accordance with local authority regulations.
- WARNING!** Brake fluid will damage paintwork. Any spillage should be flushed with water immediately.
- WARNING!** Brake fluid is flammable - keep away from sources of ignition, including hot surfaces e.g. exhaust manifold.

2. INTRODUCTION

The patented design of this pipe cutter ensures that the spring mechanism maintains the correct pressure on the pipe at all times. Features a smooth screw action and nickel plated blade for increased cutting performance.



3. OPERATING INSTRUCTIONS

- WARNING!** Before using the pipe cutter ensure that you have read and understood the Safety Instructions in Section 1.
 - 3.1 Place the pipe to be cut against the two rollers and turn the hand wheel to bring the blade up against the other side of the pipe so that the pipe is held in place under light pressure. Check that the cutter can rotate smoothly around the pipe.
 - 3.2 If the pipe to be cut is of a soft formulation, increase the pressure until the mark on the side of the sprung roller mechanism lines up with the 'SOFT' marking on the main body as shown in fig.2.
 - 3.3 If the pipe to be cut is of a hard formulation, increase the pressure until the mark on the side of the sprung roller mechanism lines up with the 'HARD' marking on the main body as shown in fig.3.
 - 3.4 When the pressure is correctly set, begin to rotate the cutter slowly around the tube. Continue to carefully rotate the cutter until the pipe is cut.
 - 3.5 If the cutter is cutting too slowly, increase the pressure by turning the handwheel by a quarter turn progressively until the pipe is cut.
- PACK OF TWO SPARE CUTTING BLADES: Part No.VS0350B

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of this product.

WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.

INFORMATION: For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.