

INSTRUCTIONS FOR: OIL FILTER CAP WRENCH SET 13PC - EUROPEAN VEHICLES

Model No: **VS7004.V2**

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

- WARNING!** Ensure Health and Safety, local authority and general workshop practice regulations are adhered to when using tools.
- DO NOT** use tools if damaged. Replace with recommended parts only. Unauthorised parts may be dangerous and will invalidate the warranty.
- Maintain tools in good and clean condition for best and safest performance.
- Use in a suitable working area. Keep area clean and tidy, and free from unrelated materials and ensure that there is adequate lighting.
- Wear approved eye protection. A full range of personal safety equipment is available from your Sealey dealer.
- Wear suitable clothing to avoid snagging. **DO NOT** wear jewellery and tie back long hair.
- Ensure that the floor is not slippery and wear non-slip shoes.
- Keep children and unauthorised persons away from the work area.
- DO NOT** attempt to start the engine whilst there is no oil filter fitted to the vehicle's engine.
- Account for all tools and parts being used and do not leave them in or near the engine.
- Ensure all pieces are returned to the case and store this in a safe, dry, childproof location.
- Dispose of waste oil in accordance with local authority regulations.
- WARNING!** DO NOT allow uncontrolled discharge of fluids which would pollute the environment.
- WARNING!** This set is for use only in the removal of filters. You should not attempt to fit a filter using this equipment, due to the risk of over-tightening which could damage the filter and lead to further complications. Consult the vehicle manufacturer's service instructions for specific instructions.

IMPORTANT: These instructions are provided as a guide only. Always refer to the vehicle manufacturer's service instructions, or a proprietary manual, to establish the correct procedure regarding the removal and fitting of an oil filter.

WARNING: The warnings, cautions and instructions discussed in this manual cannot cover all possible conditions and situations that may occur. It must be understood that common sense and caution are factors which cannot be built into this product, but must be applied by the operator.

2. CONTENTS

Here is a brief description of each piece in the set, and a list of vehicles using compatible filters.

Note: this list is a guide only and is by no means exhaustive. All parts are available separately, order through your authorised Sealey dealer.

Refer to illustration overleaf.

Part	Part No.	Description	Vehicle fitment
1.	VS7004.V2-01	66mm - 6 flutes	Fiat: Punto 1.2. Renault: Clio 1.2, Express, Kangoo, Rapid, Twingo.
2.	VS7004.V2-02	76mm - 12 flutes	Fiat: Ducato, Scudo, Ulysee. Renault: Megane, Laguna, Espace III.
3.	VS7004.V2-03	76mm - 8 flutes	Fiat: Marea. Lancia: Delta.
4.	VS7004.V2-04	86mm - 18 flutes	Audi: A6 Tdi. Citroen: Various models. Peugeot: Various models.
5.	VS7004.V2-05	86mm - 16 flutes	Renault: Clio, Rapid 1.9D, Laguna, Safrane, Espace 2.1D. VW: Golf MK III Tdi, Passat Tdi.
6.	VS7004.V2-06	92mm - 10 flutes	Volvo: S40, S60, S70, S80.
7.	VS7004.V2-07	93mm - 45 flutes	Fiat: Cinquecento, Coupe, Cromia, Panda, Regata, Ritmo, Seicento, Tempra, Tipo.
8.	VS7004.V2-08	96mm - 18 flutes	Lancia: Beta, Dedra, Kappa, Monte Carlo, Prisma, Thema, Trevi.
9.	VS7004.V2-09	106mm - 15 flutes	Audi: TDi 2.4, 2.6, 2.8L. VW: Various models.
10.	VS7004.V2-10	108mm - 15 flutes	Audi: A4 TDi. Renault: Laguna 2.2D, Safrane 2.2D, Espace 2.2D, R19 2.2D, Rapid, Megane 1.9/2.1D Tdi.
11.	VS7004.V2-11	108mm - 18 flutes	VW: Passat 97 Tdi.
12.	VS7004.V2-12	Adaptor	Fiat: Ducato 2.5D Td.
13.	VS7004.V2-13	3 legged tool	Volvo: C70, S70, S70, Tdi, TD, 850 Tdi, TD.
			Renault: Espace, Laguna, Master, Safrane, Traffic 2.4, 2.5, 2.8D, TD.
			3/8" Male Square Drive - 1/2" Female Square Drive
			65-120mm

3. APPLICATIONS

Designed primarily for European vehicles – Audi, Citroen, Fiat, Lancia, Peugeot, Renault, Volvo, VW.

Cap type filter wrenches, made from 7 and 16 gauge steel, will withstand up to 85lb.ft of torque. Designed to grip like sockets, thereby minimising the possibility of crushing filters. Includes adjustable oil filter wrench. Use with 3/8" Sq. drive, or adaptor allows use with 1/2" Sq. drive wrenches.





NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of this product.

WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.

INFORMATION: For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.



Sole UK Distributor, Sealey Group,
Kempson Way, Suffolk Business Park,
Bury St. Edmunds, Suffolk,
IP32 7AR



01284 757500



01284 703534



www.sealey.co.uk



sales@sealey.co.uk